



CR-PK05B

Ku-Band Medium-Range Pulse-Doppler Phased Array Radar

Technical Specification



Image for reference only. Finish color can be customized on request, e.g. desert tan, tactical gray, or camouflage patterns.

Document Version: V1.0 (20261008)

Version	Date	Description
V1.0	2026-10-08	Initial version.



Contents

1	Product Overview.....	3
2	Main Functions.....	4
3	Technical Specifications.....	5
3.1	Basic Performance & Accuracy.....	5
3.2	Electrical Interface.....	5
3.3	Physical & Environmental.....	5
4	Equipment Dimensions.....	7
5	Delivery List.....	8
5.1	Packing List.....	8
5.2	Logistics Dimensions.....	8
6	Maintenance.....	9
6.1	Maintenance Schedule.....	9
6.2	Maintenance Content.....	9
7	Transportation and Storage.....	10
7.1	Transportation Requirements.....	10
7.2	Storage Requirements.....	10
8	After-Sales Service.....	11



1 Product Overview

The CR-PK05B is a Ku-band medium-range phased array radar built on an all-solid-state, fully coherent, pulse-Doppler architecture, providing all-weather detection and early warning of low, slow and small (LSS) targets.

Using machine learning and AI classification based on track features and micro-Doppler features, the radar effectively detects and classifies LSS targets such as drones, light aircraft, helicopters, powered paragliders, airships and balloons at an extremely low false alarm rate.

The radar combines a one-dimensional mechanical scan plus one-dimensional electronic scan mode with a two-dimensional electronic scan directional scanning mode, providing 360° airspace surveillance and key-area detection; the two modes switch flexibly with no software change.



2 Main Functions

Detection & Coverage

- Mechanical and electronic scan modes provide 360° airspace and key-area coverage; the two modes switch flexibly with no software change;
- Rain and cloud clutter suppression enables all-weather operation;
- Instrumented range and elevation scan coverage are configurable.

Tracking & Classification

- Mechanical-scan tracking and electronic-scan TAS tracking;
- AI classification based on micro-Doppler and track features identifies drones, birds, people and vehicles;
- Strong detection performance with a low false alarm rate; stably detects maneuvering drones.

Data & Operation

- Machine learning adapts to the site environment — works on installation with no parameter tuning;
- Built-in self-positioning calibration module with automatic leveling and north-finding;
- Map-based target positioning, track display and replay with range, azimuth, elevation and velocity readouts.



3 Technical Specifications

3.1 Basic Performance & Accuracy

Item	Parameter
Frequency band	Ku band (15.7GHz ~ 16.7GHz)
Detection range	≥5km (RCS 0.01m ² , drone)
Blind zone	≤150m
Operating mode	Mechanical scan + 2D electronic scan
Search coverage	Mechanical: azimuth 0°~360°, elevation 0°~60° (mission configurable); electronic: azimuth -45°~45°, elevation 0°~60° (mission configurable)
Tracking	Mechanical-scan tracking / electronic-scan TAS
TAS tracked targets	≥6
Minimum detection altitude	≤10m
Velocity range	1m/s ~ 100m/s
Update rate	Mechanical ≤3.8s; electronic ≤3.5s (elevation coverage 30°)
Resolution	Range ≤15m, azimuth ≤6°, elevation ≤4°
Search accuracy (RMS)	Range ≤10m, azimuth ≤0.5°, elevation ≤0.4°
Tracking accuracy (RMS)	Range ≤10m, azimuth ≤0.3°, elevation ≤0.3°
Target capacity	≥500 targets

3.2 Electrical Interface

Item	Parameter
Communication	RJ45 Ethernet
Power supply	AC220V / DC24V
Power consumption	≤400W

3.3 Physical & Environmental

Item	Parameter
Weight	≤28kg (excl. power supply and tripod)
Dimensions	≤575 × 317 × 220mm
Operating temperature	-40°C ~ +70°C




Item	Parameter
Protection rating	IP66

The above specifications are typical nominal values; actual values are subject to the product contract and technical agreement.



4 Equipment Dimensions



CR-PK05B structural and installation dimensions (unit: mm)



5 Delivery List

5.1 Packing List

No.	Item	Unit	Qty
1	Radar array	Unit	1
2	Servo turntable	Set	1
3	AC/DC power adapter	Set	1
4	Ethernet cable	PC	1
5	GPS antenna (with cable)	Pair	1
6	Mounting accessories	Set	1
7	Product certificate	Copy	1
8	Operation & maintenance manual	Copy	1
9	Display & control software and communication protocol	Set	1

5.2 Logistics Dimensions

The complete set is packed in 2 cartons with a total gross weight of approximately 48kg.

No.	Contents	Carton dimensions (L×W×H, mm)	Gross weight
1	Radar host (array and servo turntable)	775 × 440 × 245	≈30kg
2	Power adapter, cables and accessories	490 × 350 × 320	≈18kg



6 Maintenance

6.1 Maintenance Schedule

The maintenance schedule may be determined according to actual service conditions, and shall in principle meet the following requirements:

- a) Perform maintenance once after transportation and before use;
- b) For radars in storage, perform maintenance every 3 months.

6.2 Maintenance Content

- a) Check the equipment appearance and completeness; check the installation for rust or cracks, installation firmness, and potential safety hazards of the installation platform;
- b) Power on and run the equipment for testing to ensure there is no abnormal radar alarm;
- c) Wipe dust and stains off the housings of the radar array face, servo turntable and power module with a dry, clean cloth;
- d) After the turntable has actually operated for 2 years, please contact the manufacturer for maintenance and replacement.



7 Transportation and Storage

7.1 Transportation Requirements

- The equipment can be transported by road, railway or air. Shock-proof packaging in dedicated packing cases is required during transportation.

7.2 Storage Requirements

7.2.1 Storage Environment

Packaged products shall be stored under the following environmental conditions to ensure their service life:

- a) Temperature
- b) Relative humidity
- c) The warehouse shall be free of acids, alkalis and other corrosive gases harmful to the equipment; during storage there shall be no strong mechanical vibration, shock or strong magnetic field.

7.2.2 Storage Life

- Unless otherwise specified in the contract, the storage period of this product shall not exceed five years from the date of receipt by the ordering party.



8 After-Sales Service

- a) The warranty period is 1 year. During this period, if the product is damaged or fails to work normally due to quality problems, the manufacturer is obliged to repair or replace it free of charge;
- b) The company responds to after-sales service requests from purchasing units within 12 hours.